



**INNOVATIVE 2 BOTTLE REFRIGERATED PROFESSIONAL SYSTEM WITH ENOMATIC® TECHNOLOGY**  
**ELEGANT DESIGN, COMPACTNESS AND EASY INSTALLATION (PLUG & PLAY)**  
**OPTION OF CONNECTING MULTIPLE SYSTEMS IN A LINE (MODULARITY)**

*Note: the image shows the model with extra side panels (black)*



- Available model: eno one 2/r 2 bottles in a line
- Wine storage temperature: 6°C - 18°C 43°F - 64°F
- Installation: "plug & play"
- Gas supply: Nitrogen E941 or Argon E938 (disposable or external cylinder; not included)
- Volumes: 1 free, 1 or 3 programmable
- Materials: stainless steel and black Gepax®
- Lighting system: LED lighting with adjustable intensity
- Bottle positioning system: self-centering lifted by pistons with gas spring
- Refrigeration system: with thermo-electric module
- Dispenser settings: via central display
- Maintenance: light signal for tap cleaning
- Optional accessories:
  - Extra side panel set (white or black color)
  - Connection kit
  - Spacer for short bottles
  - Gas canister cover
  - Dividing panel to separate bottles, 1 for white wines and 1 for red wines
  - Cylinder and pressure regulator: disposable argon canister (E938) 0,950lt - 32,12fl oz (sufficient for approx. 80 bottles)
  - Door handle with key lock

## MODULAR



**NEW POURING SYSTEM & PIPELINE CLEANING SYSTEM**

**INNOVATIVE VENTILATION SYSTEM**

**2 AREAS 1 FOR WHITE WINES AND 1 FOR RED WINES**



model	W	H	D	Weight	Electrical system requirements
eno one 2/r	27,6 cm 10,88 inch	59,7 cm 23,49 inch	35,1 cm 13,82 inch	12 kg	100-240 V   50-60 Hz   70 W (based on market destination)

[www.enomatic.com](http://www.enomatic.com)

